

NC Series

EXCELLENT FILTRATION

- Filter body made from **polyester strengthened with glass fibre for even greater pressure resistance**
- **4 models available** for 10 to 32 m³/h, for all types of pools and treatments
- Height adjusted **for use even in confined pool sheds**
- **Attractive**, its black colour goes perfectly with the existing range



6 position valve



Drain with its plug which serves as dismantling tool



Wide opening on the top for easy sand loading

NC500SE2



NC600SE2



NC780SE2



NC900SE2



Technical Specifications

Maximum working pressure	50°C
Operating pressure	0.5 – 1.5 kg/cm ²
Maximum pressure	1.6 kg/cm ²
Testing pressure	3,5 kg/cm ²
Connection	1.5" (ø 500 mm - ø 600 mm) 2" (ø 780 mm - ø 900 mm)
Tank / Laterals / Unions / Cover	Polyester+FG/ABS/ABS/ABS+FG
Granulometry of filtration media	0.4 – 0.8 mm

NC SERIES

Flow rate m ³ /h	High mm	Internal ø mm	Sand kg	Valve	Filtration area	Item	Replacement valves
10	630	500	85	1"1/2	0,20 m ²	NC500SE2	NCX07020
14	690	600	150	1"1/2	0,28 m ²	NC600SE2	NCX07020
22	830	780	300	2"	0,48 m ²	NC780SE2	NCX07021
32	950	900	450	2"	0,64 m ²	NC900SE2	NCX07022